

IMAGELINK RA Microfilm



Main features

- High-resolution sharp images
- Special anti-halation layer that improves sharpness and facilitates daylight loading
- Process-surviving anti-static backing that reduces dirt and static problems in retrieval, scanning, and duplicating equipment
- Manufactured to ISO and ANSI standards for LE-500 films
- Spectral sensitivity adjusts to red light LED 680 nm

IMAGELINK RA Microfilm is a highresolution microfilm specially formulated for the IMAGELINK 4800 Digital Archive Writer, and the IMAGELINK 9600 Series Archive Writer.

Avoid the risk and expense of digital-only records with IMAGELINK RA Microfilm. It protects your critical business records from loss or tampering by rendering a faithful analog copy of your electronic records. These non-volatile documents can be accessed electronically to authenticate current activities (such as online transactions, property records, birth and death certificates, or court records) or to support audit activities triggered by regulatory measures and legal actions. Records on IMAGELINK RA Microfilm satisfy litigation and meet regulatory and audit requirements.

This archival media has a Life Expectancy (LE) of at least 500 years when processed and stored according to the recommended practices of ISO and ANSI.

Spectral Sensitivity

Red light LED 680 nm, high speed

Resolution

630 lines/mm

Processing

IMAGELINK RA Microfilm is suitable for processing in "deep tank" microfilm processors and tabletop processors such as the IMAGELINK Archive Processor.



IMAGELINK RA Microfilm

Physical Properties

• Film type: Silver Halide

• Base: Polyester

Type	Base	Film Thickness	
	Thickness	before Processing	
Pet 6	0.062 mm	0.067 mm	
Pet 13	0.130 mm	0.135 mm	

Our History

Eastman Park Micrographics (EPM) formed in 2011 after the Dallas-based Kofile Inc. purchased Kodak's micrographic business. EPM is headquartered in Dallas, Texas.

We bring extensive experience in all aspects of document imaging to provide unique expertise in micrographics products and solutions.

Our Mission

- To continue to be the leading supplier of microfilm products worldwide
- To expand our portfolio of Reference Archive Solutions

IMAGELINK is trademark of Eastman Park Micrographics Inc.

Processing Chemicals

IMAGELINK RA Microfilm has been designed and tested to yield optimum results using common IMAGELINK processing chemicals and parameters. However, it is compatible with other standard microfilm processing equipment and high-quality chemicals. (Results may vary.)

IMPORTANT: For best results and to avoid aeration, always add chemical concentrate to water, not water to concentrate.

Replenishment Rates

Use the chart and formula provided to determine the developer and fixer replenishment rates (mL/min) by multiplying transport speed (ft/min), which is determined by dividing the path length of the developer tank in feet by the dwell time in seconds and multiplying by 60 and the appropriate processor replenishment specification (mL/linear foot). For example:

Replenishment Specification (mL/linear ft)					
	16 mm				
Type of Processor	Dev	Fix			
IMAGELINK Archive Processor	0.75	0.75			
Medium tank	0.80	0.75			
Deep tank	1.00	1.25			

Product Offerings

Туре	Width	Length	Core	Catalog No.	Case Qty
Pet 06	16 mm	66 m (215ft)	MSP	334NXDM	100
Pet 13	16 mm	30.5 m (100ft)	MSP	134NXEO	100

